













	Title	Designation	Length/Version	Diameter/ Wall Thickness	Weight	Article number
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	0,30m	38mm x 4,5mm	2,40 kg	00356/38 RIZ
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	0,50m	38mm x 4,5mm	3,20 kg	00358/38 RIZ
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	0,66m	38mm x 4,5mm	4,60 kg	00360/38 RIZ
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	0,80m	38mm x 4,5mm	5,20 kg	00362/38 RIZ
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	1,00m	38mm x 4,5mm	6,00 kg	00365/38 RIZ
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	0,50m	34mm x 4,5mm	2,75 kg	00358/34 RIZ
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	0,80m	34mm x 4,5mm	4,00 kg	00362/34 RIZ
	Adjustable Base Jack / round thread Type I	certified with round thread Type I 50 kN	0,50m	32,5mm x 4,5mm	2,25 kg	00358/32 RIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	0,30m	38mm x 4,5mm	2,40 kg	00356/38 TIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	0,50m	38mm x 4,5mm	3,20 kg	00358/38 TIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	0,66m	38mm x 4,5mm	4,60 kg	00360/38 TIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	0,80m	38mm x 4,5mm	5,20 kg	00362/38 TIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	1,00m	38mm x 4,5mm	6,00 kg	00365/38 TIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	0,50m	34mm x 4,5mm	2,75 kg	00358/34 TIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	0,80m	34mm x 4,5mm	4,00 kg	00362/34 TIZ
	Adjustable Base Jack / square thread Type I	certified with square thread Type I 50 kN	0,50m	32,5mm x 4,5mm	2,25 kg	00358/32 TIZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	0,30m	38mm x 4,5mm	2,40 kg	00356/38 RLZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	0,50m	38mm x 4,5mm	3,20 kg	00358/38 RLZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	0,66m	38mm x 4,5mm	4,60 kg	00360/38 RLZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	0,80m	38mm x 4,5mm	5,20 kg	00362/38 RLZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	1,00m	38mm x 4,5mm	6,00 kg	00365/38 RLZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	0,50m	34mm x 4,5mm	2,75 kg	00358/34 RLZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	0,80m	34mm x 4,5mm	4,00 kg	00362/34 RLZ
	Adjustable Base Jack / round thread Type L	certified with round thread Type L 50 kN	0,50m	32,5mm x 4,5mm	2,25 kg	00358/32 RLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	0,30m	38mm x 4,5mm	2,40 kg	00356/38 TLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	0,50m	38mm x 4,5mm	3,20 kg	00358/38 TLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	0,66m	38mm x 4,5mm	4,60 kg	00360/38 TLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	0,80m	38mm x 4,5mm	5,20 kg	00362/38 TLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	1,00m	38mm x 4,5mm	6,00 kg	00365/38 TLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	0,50m	34mm x 4,5mm	2,75 kg	00358/34 TLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	0,80m	34mm x 4,5mm	4,00 kg	00362/34 TLZ
	Adjustable Base Jack / square thread Type L	certified with square thread Type L 50 kN	0,50m	32,5mm x 4,5mm	2,25 kg	00358/32 TLZ

	Title	Designation	Length/Version	Diameter/ Wall Thickness	Weight	Article number
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	0,30m	38mm x 4mm	2,40 kg	00356/38 RIG
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	0,50m	38mm x 4mm	3,20 kg	00358/38 RIG
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	0,66m	38mm x 4mm	4,60 kg	00360/38 RIG
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	0,80m	38mm x 4mm	5,20 kg	00362/38 RIG
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	1,00m	38mm x 4mm	6,00 kg	00365/38 RIG
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	0,50m	34mm x 4mm	2,75 kg	00358/34 RIG
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	0,80m	34mm x 4mm	4,00 kg	00362/34 RIG
	Adjustable Base Jack / round thread Type I	as per DIN 4225 round thread Type I 50 kN	0,50m	32,5mm x 4mm	2,25 kg	00358/32 RIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	0,30m	38mm x 4mm	2,40 kg	00356/38 TIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	0,50m	38mm x 4mm	3,20 kg	00358/38 TIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	0,66m	38mm x 4mm	4,60 kg	00360/38 TIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	0,80m	38mm x 4mm	5,20 kg	00362/38 TIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	1,00m	38mm x 4mm	6,00 kg	00365/38 TIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	0,50m	34mm x 4mm	2,75 kg	00358/34 TIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	0,80m	34mm x 4mm	4,00 kg	00362/34 TIG
	Adjustable Base Jack / square thread Type I	as per DIN 4225 square thread Type I 50 kN	0,50m	32,5mm x 4mm	2,25 kg	00358/32 TIG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	0,30m	38mm x 4mm	2,40 kg	00356/38 RLG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	0,50m	38mm x 4mm	3,20 kg	00358/38 RLG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	0,66m	38mm x 4mm	4,60 kg	00360/38 RLG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	0,80m	38mm x 4mm	5,20 kg	00362/38 RLG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	1,00m	38mm x 4mm	6,00 kg	00365/38 RLG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	0,50m	34mm x 4mm	2,75 kg	00358/34 RLG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	0,80m	34mm x 4mm	4,00 kg	00362/34 RLG
	Adjustable Base Jack / round thread Type L	as per DIN 4225 round thread Type L 50 kN	0,50m	32,5mm x 4mm	2,25 kg	00358/32 RLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	0,30m	38mm x 4mm	2,40 kg	00356/38 TLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	0,50m	38mm x 4mm	3,20 kg	00358/38 TLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	0,66m	38mm x 4mm	4,60 kg	00360/38 TLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	0,80m	38mm x 4mm	5,20 kg	00362/38 TLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	1,00m	38mm x 4mm	6,00 kg	00365/38 TLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	0,50m	34mm x 4mm	2,75 kg	00358/34 TLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	0,80m	34mm x 4mm	4,00 kg	00362/34 TLG
	Adjustable Base Jack / square thread Type L	as per DIN 4225 square thread Type L 50 kN	0,50m	32,5mm x 4mm	2,25 kg	00358/32 TLG

	Title	Designation	Length/Version	Diameter/ Wall Thickness	Weight	Article number
	Adjustable Base Jack Moveable	Hot Dip Galvanized Adjustable Base Jack moveable / swiveling 25 kN	0,50m	38mm x 4mm	3,00 kg	P-00361
	Adjustable Base Jack Moveable	Hot Dip Galvanized Adjustable Base Jack moveable / swiveling 25 kN	0,80m	38mm x 4mm	3,20 kg	P-00362
	Adjustable Base Jack Moveable	Hot Dip Galvanized Adjustable Base Jack moveable / swiveling 25 kN	0,50m	34mm x 4mm	2,75 kg	P-00361-34
	Adjustable Screw Jack with Half Coupler	Adjustable Screw Jack with Half Coupler	0,50m	38mm x 4mm	2,70 kg	10363
	U-Head Screwjack	Head Spindle with U-profile	0,50m	38mm x 4mm	5,80 kg	363
	Adapter for Lattice Girder	Hot Dip Galvanized Adapter for Lattice Girder	0,50m	38mm x 4mm	5,90 kg	638
	Adjustable screw jack with castor incl. lock	Adjustable Screw Jack with Castor - 3 kN	150mm	38mm x 4mm	7,50 kg	393
	Adjustable screw jack with castor incl. lock	Adjustable Screw Jack with Castor - 10 kN	200 mm	38 mm x 4mm	8,50 kg	390
	Base Plate	Base Plate	Hot Dip Galv.	150mm x 150mm	0,800 kg	90
	Base Plate	Base Plate	Black	150mm x 150mm	0,800 kg	000090-S
	Adjusting Nut Type I	Adjusting Nut Type I	Hot Dip Galv.	38mm	0,400 kg	00350-1
	Adjusting Nut Type L	Adjusting Nut Type L	Hot Dip Galv.	38mm	0,800 kg	00350-2
	Adjustable Base Jack to sustain Framework	Hot Dip Galvanized Adjustable Base Jack to sustain framework	850mm	48mm x 4mm	5,80 kg	E-005
	Head Spindle with crosshead for Framework	Hot Dip Galvanized Head Spindle with crosshead to sustain framework	800mm	48mm x 4mm	8,50 kg	E-006